



METAL-FACH

METAL-FACH RAVEN OPTI SPEED TILLERS

Polish-made high speed tiller with heavy duty pipe roller
Ideal for pre-sowing cultivation, weed control and shallow cultivation.

A reliable solution for ground preparation, works efficiently to help you achieve better results in the field.

RAVEN OPTI 710 SERIES

FEATURES

- Heavy Duty frame construction
- Heavy duty 1000mm dia pipe roller
- Hydraulic folding
- Simex (high grade steel) disc arms
- Rubber shock absorbers
- Heavy duty 20" (500mm) discs with large scallop discs
- 20" (500mm) edge discs with adjustment to reduce any ridges
- ICF maintenance free balls to ensure long life and trouble free operation
- Adjustable spring tyres for break clumps and fluff weeds for surface
- Twin cylinder hydraulic depth control with easy to set height selection
- Reversed discs to maintain cutting angle as discs wear, reduces side load on bearings and provides greater counterforce on discs and adjusted arms for soil to pass through.

OPTIONS

- Grading for forward version
- Other roller options
- Side discs

SPECIFICATIONS

Model	SP1600-10	SP1600-150	SP1600-200	SP1600-250
Working width (m)	4.5	5.5	6.5	7.5
Number of discs per edge	16	18	18	16
Disc size	1600 x 1600	1600 x 1600	1600 x 1600	1600 x 1600
Disc spacing (mm)	1000	1000	1000	1000
Hydraulic independent lift	YES, 2000	No, 2000	YES, 2000	2000, 2000
Weight of unit without roller (kg)	2620	2950	3600	3970



SALBAG
ROLLERS • ROLLERS • ROLLERS • ROLLERS

Headquarter WZP
 81-1000 1000
 tel: +49 914 9111-111
 e: info@salbag.com or
www.salbag.com



METAL-FACH

METAL-FACH RAVEN OPTI SPEED TILLERS

Polish made high speed tiller with heavy duty pipe roller.
Ideal for pre-sowing cultivation, weed control and residue cultivation.

A reliable solution to general preparation, works efficiently to help you achieve better results in the field.

RAVEN OPTI 740 SERIES

FEATURES

- Heavy Duty frame construction
- Twin cylinder hydrostatic depth control with easy to set height roller bars
- Heavy duty 100mm dia. pipe roller
- Heavy duty 22" (560mm) twin thick large cutting discs
- 22" (560mm) edge discs with adjustment to reduce any ridges
- S&P maintenance free hubs, to ensure long life and trouble-free operation
- Rubber shock absorbers
- Titanium (high grade steel) disc arms
- Adjustable spring tyres to break clumps and fluff weeds to surface
- Reinforced discs to maintain cutting angle as discs wear, reduces side load on bearings and provides greater run in between disc and adjusted arm for soil to pass through.

OPTIONS

- Different roller options
- Side discs

SPECIFICATIONS

Model	SR1500/20	SR1500/30	SR1500/40	SR1500/50	SR1500/60
Working width (m)	2.8	3	3.8	4	5
Number of rollers per edge	20	24	28	32	40
Drive roll	Roller driven	Roller driven	Roller driven	Roller driven	Roller driven
Drive roll spacing (mm)	800	800	800	800	800
Hydraulic spreading width	20-1700	20-1700	200-1700	200-1700	200-2000
Weight of unit without roller (kg)	1200	1600	1900	1900	2300



SALIBAG

Roller Technology - Soil Compaction - Soil Care

Headquarter: 9030

50 642-1000

info@salibag.com.au

www.salibag.com.au